NO.

73-G-5



## Austin MG

MODELS:

April, 1973

SUBJECT:

PRE-DELIVERY INSPECTION CALIFORNIA DEALERS ONLY FORM # SER.73

ALL

The following operations have been checked prior to dealer delivery of all new vehicles:

Adjust as required
Dwell
Ignition timing advance and retard
Idle RPM and choke settings

Therefore, as indicated with a red asterisk under OSCILLOSCOPE CHECK on the attached Pre-Delivery Inspection Form #SER.73, these operations must be deferred until the 1,000 mile service.

REK



## PRE-DELIVERY INSPECTION

1	BRITISH
	(A)
ī	LEYLAND

SERIAL NO	R/O NO. & DATE		
ENGINE NO	IGNITION KEY NO.	LEYL	
MAKE/MODEL	DOOR KEY NO		
OWNER	TRUNK KEY NO		
ADDRESS	COLOR/NOTRIM/NO		
	Tire   Radial   Type   Whitewall	Cross Ply Black Wall	
INTERIOR	ENGINE COMPARTME	NT	
Check operation of and adjust as necessary	Check security, chafing, leaks and adjust as no	ecessary	
All instruments	All water, oil, fuel, freon, vacuum clutch a	nd brake hoses	
All switches and controls	and pipes		
All safety devices	All fluid levels		
Clutch pedal	Antifreeze protection to		
Shift control	Battery specific gravity		
☐ Brake pedal	☐ Electrical connections		
Parking brake control	Manifolds		
Seats and mountings	All drive belts		
Seat belts and anchorage points	Lubricate choke and throttle linkage		
	Charging system		
Interior and exterior lighting	in thinging system		
All doors, hood, trunk, window controls and locks	OSCILLOSCOPE CHEC	K	
UNDERCARRIAGE	* Adjust as required	* State of	
Charle for convite shefing looks and adjust as pagernary	* Dwell	California dealers	
Check for security, chafing, leaks and adjust as necessary	Spark plugs (cruise and unload)	refer to	
Front suspension and steering	★ ☐ Ignition timing advance and retard	service bulletin 73G	
Engine, transmission, drive line and rear axle	★ ☐ Idle RPM and choke settings		
Rear suspension	CO% HCP.P.M. readings		
Water, clutch, brake, fuel and vacuum hoses and pipes	CO		
Exhaust system	ROAD TEST		
Adjust clutch and brake			
Grease all lubrication points	Check for correct performance:		
Check all fluid levels	Suspension Instrumentation He		
EVTERIOR	system   Locate and rectify any rattles, vi	brations or squeaks	
EXTERIOR  Tighten all hub extensions and wheel nuts	FINAL PREPARATION		
Check tires specification and adjust pressures including spare	Remove all flammable protective shipping	materials	
A STATE OF THE PARTY OF THE PAR		THATAITAIS	
Check contents and operation of all tool kit items	☐ Clean engine ☐ Vacuum and clean interior		
Check owners literature pack			
Install all items that were not fitted prior to shipment	Wash and polish exterior		
Check and adjust front wheel alignment	Inspect interior and exterior for damage to	upnoistry,	
Align head lamps	floor coverings, paint, chrome and glass		
Check fit of convertible/hardtop and tonneau covers	Place spare keys with owners literature pa	CK	
REMARKS:	ACCESSORIES TO BE FITTED:		
I CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO SAFETY AND EMISSION REQUIREMENTS			
DEALER STAMP	MECHANIC		
	SERVICE MANAGER		



## PRE-DELIVERY INSPECTION



SERIAL NO.	R/O NO. & DATE_		
ENGINE NO.	IGNITION.KEY NO		
MAKE/MODEL			
OWNER			
ADDRESS	COLOR/NO	TRIM <b>/</b> NO	
TIRE MA	KE <b>/</b> SIZE	Tire   Radial	Cross Ply
INTERIOR		IGINE COMPARTMEN	
Check operation of and adjust as necessary		chafing, leaks and adjust as ne	
All instruments	All water, oil	, fuel, freon, vacuum clutch ar	d brake hoses
All switches and controls	and pipes		
All safety devices	All fluid level	ls	
Clutch pedal	Antifreeze pr	otection to	
Shift control	☐ Battery speci		
Brake pedal	Electrical cor	- · ·	
		inections	
☐ Parking brake control	☐ Manifolds		
Seats and mountings	All drive belt		
Seat belts and anchorage points		oke and throttle linkage	
Interior and exterior lighting	L Charging syst	em	
All doors, hood, trunk, window controls and locks			
	09	SCILLOSCOPE CHECI	<
UNDERCARRIAGE	*Adjust as require	.d	
		·u	State of
Check for security, chafing, leaks and adjust as necessary	200		California deale
Front suspension and steering		cruise and unload)	refer to
Engine, transmission, drive line and rear axle		ng advance and retard	service bulletin 7
Rear suspension	Idle RPM and	l choke settings	
Water, clutch, brake, fuel and vacuum hoses and pipes	□ со% н	ICP.P.M. readings	
Exhaust system			
Adjust clutch and brake		ROAD TEST	
Grease all lubrication points			<b>□</b> -
<del></del>		t performance: Engine	
Check all fluid levels ~		Instrumentation Hea	-
<u>_i</u>	system 🗀 Loc	cate and rectify any rattles, vib	rations or squeaks
EXTERIOR			
Tighten all hub extensions and wheel nuts	. · FI	<b>INAL PREPARATION</b>	
Check tires specification and adjust pressures including spare	Pomovo all fl	ammable protective shipping r	
Check contents and operation of all tool kit items	<del></del>	animable protective snipping r	naterials
·	Clean engine		
Check owners literature pack	☐ Vacuum and		
Install all items that were not fitted prior to shipment	Wash and pol		
Check and adjust front wheel alignment	Inspect interi	or and exterior for damage to	upholstry,
Align head lamps	floor coverings, paint, chrome and glass		
	Place spare ke	eys with owners literature pack	c sta
Check fit of convertible/hardtop and tonneau covers			
	ACCESSORIES TO	BE FITTED:	
	ACCESSORIES TO	BE FITTED:	
	ACCESSORIES TO	BE FITTED:	
	ACCESSORIES TO	BE FITTED:	
CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO			
CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO			· · · · · · · · · · · · · · · · · · ·
Check fit of convertible/hardtop and tonneau covers  REMARKS:  I CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO SAFETY AND EMISSION REQUIREMENTS  DEALER STAMP	MANUFACTURER'S	SPECIFICATIONS AND ME	
CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO SAFETY AND EMISSION REQUIREMENTS	MANUFACTURER'S		
CERTIFY THAT THE VEHICLE DESCRIBED CONFORMS TO SAFETY AND EMISSION REQUIREMENTS	MANUFACTURER'S	SPECIFICATIONS AND ME	